

Power Breezer



Breezer Oasis



TECHNICAL SPECIFICATIONS

	VOLTS	PART NUMBER	VOLTS	PART NUMBER
	110V	PB10-A-06-B	110V	IG-AB10-A-01-B
Cooling Ability	Up to 27°F (15°C)		Up to 27°F (15°C)	
Area of Coverage (Optimal)	Up to 3,000 sq. ft. (279m ²)		Up to 1,500 sq. ft. (140m ²)	
Effective Distance	Up to 80 feet (24 meters)		Up to 40 feet (12.2 meters)	
Oscillation	Yes		Yes	
Integrated Water Container	Yes - 100 gallons (378 liters) Hose connection not required.		Yes - 19 gallons (72 liters) Hose connection not required.	
Operating Time	4-5 days running 10-12 hrs/days		18 hours operating time per fill	
Effective Water Vaporization	0.1-2 Gallons/Hour (0.4L-7.6L/Hour)		0.1-.95 Gallon/Hour (0.4L-3.6L/Hour)	
Electric Consumption	Avg. 9 Amps, 990 Watts (110V Unit); Avg. 5 Amps, 1,100 Watts (220V Unit)		Avg. 6 Amps, 660 Watts (110V Unit); Avg. 4 Amps, 880 Watts (220V Unit)	
Air Flow	14,000 CFM (23,786 m ³ /hr)		7,000 CFM (11,893 m ³ /hr)	
Height	46" (116.8cm) stored, 70" (177.8cm) mounted		66" (168cm)	
Width	29.5" (75cm)		25" (64cm)	
Depth	42" (107cm) stored, 51.5" (130.8cm) mounted		27" (69cm)	
Weight (without water)	220 lbs. (99.8kg)		135 lbs. (61kg)	
Power Source	110V or 220V (Type G Plug)		110V or 220V (Type G Plug)	
Motor	1 hp E		1 hp E	
Technology	Unique atomization technology		Unique atomization technology	
Wheels	10" (25.4cm) and 8" (20cm) heavy duty locking wheels/castors		8" (20cm) and 4" (10.2cm) medium duty wheels/locking castors	
Hard case for shipping and transport	Yes - Integrated into design		No	
Certifications	OSHA Compliant, ETL Certified, NOM Certified, CE Compliant (220V unit)		OSHA Compliant, ETL Certified, NOM Certified	
Warranty	2 Years		1 Year	

Breezer Mobile Cooling

550 SW 12th Avenue, Suite 550
Deerfield Beach, FL 33442 U.S.A.

BreezerCooling.com | sales@breezercooling.com

U.S. 844.233.5673 | Int'l. 001 954 418 4530