

## Power Breezer Titan



## O2 Titan



## TECHNICAL SPECIFICATIONS

|                                      | VOLTS   | GOVERNMENT PART NUMBER               | VOLTS   | GOVERNMENT PART NUMBER                     |
|--------------------------------------|---|--------------------------------------|---|--|
|                                      | <b>110V</b><br><b>220V</b>  | <b>PB10-A-1B</b><br><b>PB20-A-1B</b> | <b>110V</b><br><b>220V</b>  | <b>MG-AB10-A-01</b><br><b>MG-AB20-A-01</b> |
| Cooling Ability                      | Up to 27°F (15°C)   |                                      | Up to 27°F (15°C)   |  |
| Area of Coverage (Optimal)           | Up to 3,000 sq. ft. (279m <sup>2</sup> )  |                                      | Up to 1,500 sq. ft. (140m <sup>2</sup> )  |  |
| Effective Distance                   | Up to 80 feet (24 meters)   |                                      | Up to 40 feet (12.2 meters)   |  |
| Oscillation                          | Yes   |                                      | Yes   |  |
| Integrated Water Container           | Yes - 80 gallons (303 liters)<br>Hose connection not required.                            |                                      | Yes - 40 gallons (151 liters)<br>Hose connection not required.                      |  |
| Operating Time                       | 4-5 days running 10-12 hrs/days   |                                      | 2-3 days running 10-12 hrs/days   |  |
| Effective Water Vaporization         | 0.1-2 Gallons/Hour (0.4L-7.6L/Hour)   |                                      | 0.1-.95 Gallon/Hour (0.4L-3.6L/Hour)  |  |
| Electric Consumption                 | Avg. 9 Amps, 990 Watts (110V Unit);<br>Avg. 5 Amps, 1,100 Watts (220V Unit)               |                                      | Avg. 6 Amps, 660 Watts (110V Unit);<br>Avg. 4 Amps, 880 Watts (220V Unit)           |  |
| Air Flow                             | 14,000 CFM (23,786 m <sup>3</sup> /hr)  |                                      | 10,000 CFM (16,990 m <sup>3</sup> /hr)  |  |
| Height                               | 46" (116.8cm) stored,<br>70" (177.8cm) mounted  |                                      | 41.75" (106cm) stored<br>63.3" (161cm) mounted                                      |  |
| Width                                | 29.5" (75cm)  |                                      | 26.3" (67cm)  |  |
| Depth                                | 42" (107cm) stored,<br>51.5" (130.8cm) mounted  |                                      | 37.0" (94cm) stored<br>44.1" (112cm) mounted  |  |
| Weight (without water)               | 220 lbs. (99.8kg)   |                                      | 176 lbs. (80kg)   |  |
| Power Source                         | 110V or 220V (Type G Plug)  |                                      | 110V or 220V (Type G Plug)  |  |
| Motor                                | 1 hp E  |                                      | 1/3 hp E  |  |
| Technology                           | Unique atomization technology   |                                      | Unique atomization technology   |  |
| Highly durable casters               | 10" (25.4cm) and 8" (20cm)<br>rugged locking wheels/casters                               |                                      | 8" (20.3cm) and 6" (15.2cm)<br>rugged wheels/locking casters                        |  |
| Hard case for shipping and transport | Yes - Integrated into design  |                                      | Yes - Integrated into design  |  |
| Certifications                       | OSHA Compliant, ETL Certified,<br>NOM Certified, CE Compliant (220V unit)<br>MIL-STD 810G |                                      | OSHA Compliant, ETL Certified,<br>(NOM, CE, MIL-STD 810G<br>Certifications Pending) |  |
| Warranty                             | 2 Years   |                                      | 2 Years   |  |

### Breezer Mobile Cooling

550 SW 12th Avenue, Suite 550  
Deerfield Beach, FL 33442 U.S.A.

BreezerCooling.com | sales@breezercooling.com

U.S. 844.233.5673 | Int'l. 001 954 418 4530